



Docket No.: 254659US0X PCT

IFW



COMMISSIONER FOR PATENTS
ALEXANDRIA, VIRGINIA 22313

ATTORNEYS AT LAW

RE: Application Serial No.: 10/501,713

Applicants: Volker HENNIGE, et al.

Filing Date: July 19, 2004

For: CERAMIC MEMBRANE BASED ON A
SUBSTRATE CONTAINING POLYMER OR
NATURAL FIBRES, METHOD FOR THE
PRODUCTION AND USE THEREOF

Group Art Unit: 1771

Examiner: Elizabeth M. Cole

SIR:

Attached hereto for filing are the following papers:

Response to Restriction and Election of Species Requirement

Our check in the amount of \$0.00 is attached covering any required fees. In the event any variance exists between the amount enclosed and the Patent Office charges for filing the above-noted documents, including any fees required under 37 C.F.R. 1.136 for any necessary Extension of Time to make the filing of the attached documents timely, please charge or credit the difference to our Deposit Account No. 15-0030. Further, if these papers are not considered timely filed, then a petition is hereby made under 37 C.F.R. 1.136 for the necessary extension of time. A duplicate copy of this sheet is enclosed.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.

Norman F. Oblon

Daniel R. Evans, Ph.D.

Registration No. 55,868

Customer Number

22850

(703) 413-3000 (phone)
(703) 413-2220 (fax)



DOCKET NO: 254659US0X PCT

IN THE UNITED STATES PATENT & TRADEMARK OFFICE

IN RE APPLICATION OF :

VOLKER HENNIGE, ET AL.

: EXAMINER: ELIZABETH M. COLE

SERIAL NO: 10/501,713

:

FILED: JULY 19, 2004

: GROUP ART UNIT: 1771

FOR: CERAMIC MEMBRANE BASED
ON A SUBSTRATE CONTAINING
POLYMER OR NATURAL FIBRES,
METHOD FOR THE PRODUCTION AND
USE THEREOF

RESPONSE TO RESTRICTION AND ELECTION OF SPECIES REQUIREMENT

Responsive to Official Action dated March 21, 2006, Applicants elect with traverse, Group I, Claims 1-4, 6-10, 26 and 27, drawn to membrane and a method of using the membrane. In addition as a single species, Applicants elect a membrane as obtained by treating a nonwoven having a porosity of more than 50% and a thickness of 30 μ m as described in Example 7, with traverse.